

High Performance Multipurpose Adhesives

Product	Viscosity	Solid %	Application
Top Bond 126	500±1500cps	54±1%	High performance heat resistant water based adhesive for manufacturing of insulation ducts, flexible air hose. Can bond to metal, glass fiber, wood, foam etc.
Top Bond Ht C9	Very thick paste	—	Aerospace grade epoxy adhesive for manufacturing of aerospace grade tiles. Heat resistance of 1400 degree C.
Top Bond Cr 18 2k	Very thick paste	—	Aerospace grade 2 component adhesive for pasting of tiles to metal. Heat resistance of upto 1500 Degree C.
Chipko DP3	10000±1000 cps	53±1%	Waterproof adhesive to bond stone to fabric. Excellent product for handicraft industries. This Green adhesive is food grade (indirect contact) and follows EN norms for the same.
Chipko NL2	17±2 secs	59±1%	Water based adhesive for bonding of leather to leather for premium leather industry. Used for manufacturing of premium brands shoes, bags, wallets etc. Reach compliant, sprayable product for export.
Chipko NL3	17±2 secs	62±1%	Water based adhesive for bonding of leather to leather for premium leather industry, for no stitch application. Used for manufacturing of premium heavy bags, belts, saddles etc. REACH compliant, sprayable product for export.
Chipko NL2	1800±400cps	26±1%	Solvent borne Rubber adhesive for applications where 170 degree heat resistance is required.
Chipko WS900	3600±500 cps	39±1%	Food grade(indirect contact) adhesive for manufacturing of paper straw.



Water Based Pressure Sensitive Adhesives

**BHIWADI
POLYMERS**

Manufactures Range of Water Based Pressure Sensitive Adhesive. This Series is Completely Suitable for Application in BOPP Packaging Tapes, Holographics Labels, Stickers, Label Stocks, Protective Films,

Envelope Flaps and other Allied Uses. substrate



Product	Grade	Viscosity, at 25° C	pH	Solids%	Application	Specific Advantages
Water Based Pressure Sensitive Adhesives	PST 60	28±2 secs	7.0±0.5	58±1	Suitable for Self Adhesive BOPP Tape & Holographic Labels.	Good Tack & Non Transferable
	PST 52	16±2 secs	7.0±0.5	52±1		
	PS 5520	1300±200 cps	6.0±1.0	52±1	Suitable for Stickers & Label Stock.	
	PS 5570	7500±500 cps	6.0±1.0	52±1		
Window Patching Adhesive	PST 55 (PF)	17±2 secs	8.0±0.5	51±2	Used on LDPE Films for Acrylic, Glass & other surfaces to protect from Scratch, Cutting, Abrasion etc.	Non-transferable, clear adhesive coating & clean removability.

